

BaleFeeder

The BF8000SL is designed to feed out round bales up to 6' in diameter and weighing up to 2,500 lbs. The BF8000SL is equipped with a hydraulic loading arm and two prong bale spear, to lift and place the bale on the table. The loading arm can also be used to carry a second bale to the field. Once placed on the table, an apron chain rotates the bale as the drum's fingers unravel the hay. As the core of the bale is approached, the table can be tilted increasing contact between the bale and the drum ensuring the entire bale is fed out.

Specifications	BF8000SL
Unit Type	Trailed, Self Loading
Height	66"
Width	119"
Length	221"
Weight	3,700 lbs.
For use with	Hay, Straw, Baleage, Silage
Bale Size	4-5' Wide up to 6' Round
Bale Weight	2,500 lbs. Maximum



Self Loading

The BF8000SL has a hydraulic self loading design removing any need for additional equipment to load bales onto the BaleFeeder table.



Bale Spear Position Indicator

The mechanical loading arm position indicator lets you know when the bale spears are in the ideal position for loading different sizes of bales, or when the loading arm is in position for transporting.



Live Floor with Apron Chain

The live floor has steel slats, driven by two robust apron chains, driving the bale towards the rotor with ease.



Table Angles up to 22.5°

The live floor hydraulically angles up to 22.5° ensuring the last of each bale gets placed onto the field where you want it.



Retractable Fingers

The BaleFeeder's drum uses retractable fingers to grab and fluff the bale on the table side, while retracting back into the drum on the unloading side preventing material from being pulled back under the drum back onto the table.



Storage Box

A storage box can be added to the tongue of the BF8000SL. It's the ideal place to discard both net and bale wrap when in the field.



Implement Tires

400/60-15.5 implement tires



Tractor Lug Tires

31x15.50-15 tractor lug tires.

Tubeline Manufacturing Ltd.

6455 Reid Woods Drive Elmira, Ont. Canada N3B 2Z3 P. 1.888.856.6613 • F. 519.669.5808 sales@tubeline.ca • www.tubeline.ca