

NITRO 275RS

NEW
2018



Built with smaller operations in mind, the Nitro 275RS is constructed with top grade materials to handle real day-to-day farming. With standard features including robust apron chains, hungry vertical beaters, and optional mechanically operated tail lights that open and close along with the adjustable guillotine endgate, you can rest assured that the Nitro 275RS will not only provide the consistent spread you'll need, but also limit your time in the field.

Nitro 275RS Specifications**

Carrying Capacity	10 Ton
Heaped (cu. ft.)	293
Struck Level (cu. ft.)	220
Inside Dimensions (Inside width between flare 102.5")	62.5"W x 34.5"D x 143"L
Overall Length	23.5'
Overall Outside Width (Single/Tandem Axle)	118"/117"
Loading Height	69"
Wheel Hub Capacity (Single Axle)	16,000lbs (10-bolt) x2
Wheel Hub Capacity (Tandem Axle)	12,000lbs (8-bolt) x4
Beater Diameter	34"
Beater Speed	420 RPM
PTO Speed	1000 RPM
Apron Chain Link Diameter	5/8"
Shipping Weight	8,800lbs.
Required Tractor PTO HP	80
Brakes Available	Yes

* Production model may vary. Specifications subject to change without notice.

** Capacities determined by ASAE Std S324.1

Features

- Heavy 5/8" logging chain (Limited Lifetime Warranty)
- Tandem or single axle options
- Overrunning Clutch reduces stress on gearbox
- Torque Limiter reduces driveline damage
- PTO with CV shaft
- Polyboard Floor

Available Tires



425 x 22.5 (16 x 22.5)

550/45 - 22.5

Tires available for either single or tandem axle applications.

TUBE-LINE

www.tubeline.ca 1.888.856.6613

