



TUBELUNE





HEAVY-DUTY CHAIN DRIVE



Transfers power evenly from PTO to both rollers, ensuring constant tension at any roller setting which is achieved by an exclusive pivoting jack shaft. Harvesting premium quality hay is often out of your control, relying on good weather and a lot of luck. Producers are now seeing the benefits of conditioning hay for consistently better results. The Tubeline Accelerator is your fastest way to better hay by reducing drying time, creating greener, sweeter and softer hay.

The Accelerator's easy operation conditions hay by simply running it through adjustable steel crimping rollers, up to 15 mph. This process cracks the hay stems without knocking off the leaves. Conditioning also fluffs the hay, allowing air to flow through the swath, for faster and more even drying from top to bottom. Speed up your operation with the Tubeline Accelerator producing better hay, faster drying time and bigger profits. Contact your authorized Tubeline dealer for more details.

ADJUSTABLE STEEL-PADDLE ROLLERS



Increase or decrease amount of desired crimp by easily adjusting top roller up or down. Solid roller construction ensures consistency of crimping every time.

WALKING-BEAM TANDEM AXLE



(Available on 7500T & 9500T) Improves smoother travel on bumpy fields by reducing bouncing, keeping unit in better control.

SPREADER (OPTIONAL)



Evenly distributes hay in wide rows where both sun and wind touch it at once.



Lowered - Low ground clearance ensures no hay is missed

ACCELERATOR BOOT

Raised - Transport Position

SPECIFICATIONS

SPECIFICATIONS	7500S	7500T	9500T	
Roll Width	7'	7'	9'	
Paddles Per Roll	9	9	9	
PTO Speed	540/1000	540/1000	540/1000	
Axle	Single	Tandem	Tandem	
Width	126"	132"	156"	
Length	153"	153"	153"	
Weight (lbs.)	2750	2900	3000	

